

DS-425

Weighing scale



***High precision weighing scale
with user-friendly features,
designed for a variety of
applications***



DS-425
Weighing scale

Accurate, fast, functional and easy use



Check weighing with filling function



Counting function



Selectable weight units (g, kg, oz or lb.)



- High display resolution: 1/30,000
- resolution to 0.01g
- Standard RS-232C I/F
- Digital tare subtraction

Specifications

Capacity and Scale interval

	1/3000	1/6000	1/15000	1/30000
300g	e=0.1g	e=0.05g	e=0.02g	e=0.01g
600g	e=0.2g	e=0.1g		e=0.02g
1.5kg	e=0.5g		e=0.1g	e=0.05g
3kg	e=1g	e=0.5g	e=0.2g	e=0.1g
6kg	e=2g	e=1g		e=0.2g
15kg	e=5g		e=1g	e=0.5g

Dimensions: 256(W)×321(L)×80(H)mm/
10.08(W)×12.64(L)×3.15(H)inch

Options: Built-in printer kit

Internal resolution: 1/300,000
Display resolution: 1/30,000
Weight sensor: Load cell
Weight display: 5 digits
Power source: AC 100/110/117V, 220/230/240V
50/60 Hz (Factory Preset)
Power consumption: 14W (with printer)
Operating temperature: 5°C to 35°C / 41°F to 95°F
Operating humidity: 85%RH Max. (Non-condensing)
Net weight: 3.5kg/7.71 lb
Standard RS-232C I/F with Din 8 pin connector

ITEM WEIGHT UNIT

GROSS: 0.9315kg
NET: 0.9312kg
TARE: 0.0000kg



DS-425 with printer

*Specifications are subject to change without notice.

TERAOKA SEIKO CO., LTD.

13 12 KUGAHARA 5 CHOME OHTA KU,
TOKYO 146-8580 JAPAN
TEL:+81-3-3752-2131 FAX:+81-3-3752-2801